



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265  
TEL: (315) 472-5270  
FAX: (613) 226-2802

TEL: 1-800-265-6681  
FAX: 1-800-561-1970


e-mail: info@avtechpulse.com  
http://www.avtechpulse.com/

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4  
TEL: (613) 226-5772  
FAX: (613) 226-2802

PERFORMANCE CHECKSHEET

Model: AV-156A-B  
S.N.: 10850  
Date: January 5, 2004


Rise Time Test, to 2.5 Ohms:



Top: OUT, 4.5A amplitude with 0.5A offset into 2.5Ω  
10ms PW, 20 Hz PRF, 5V/div, 4 us/div  
Bot: Monitor output into 10kΩ load, 2V/div, 4 us/div

- a) Output Signal Amplitude: 0-5A
- b) DC Offset: 0 - 500 mA
- c) Pulse Width: 10 us - 10 ms
- d) Rise Time: < 4 us (for  $R_L < 3\Omega$ )
- e) Fall Time: < 4 us (for  $R_L < 3\Omega$ )
- f) PRF: 0.1Hz - 10 kHz
- g) Jitter, Stability: OK
- h) Prime Power: 120/240V AC, 50-60 Hz.

High Impedance Load Test:



Top: OUT, 100 mA amplitude into 80Ω  
300 us PW, 20 Hz PRF, 2V/div, 40 us/div  
Bot: Monitor output into 10kΩ load, 50 mV/div, 40 us/div

References levels: 10%, 90%.