



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVO-2W-B-PN  
Type: High Speed Laser Diode Driver  
S.N.: 11616  
Date: November 1, 2006

Output Amplitude: 0 to ±10A, to 6.2Ω  
Pulse Width (FWHM): 4 – 50 ns  
Rise Time (20%-80%): ≤ 2 ns  
Fall Time (80%-20%): ≤ 2 ns  
PRF: 1 Hz - 20 kHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

10 kHz, 50 ns, +60V into a load consisting of 5.1 Ohms in series with a 1N5819 diode. Measured with a 711S current probe (5A/div). The rise and fall times are degraded slightly by the inductance introduced by the 711S probe.

10 kHz, 50 ns, -60V into a load consisting of 5.1 Ohms in series with a 1N5819 diode. Measured with a 711S current probe (5A/div). The rise and fall times are degraded slightly by the inductance introduced by the 711S probe.

10 ns/div, 5 A/div (50 mV × 40 dB × 1A/V):



10 ns/div, 5 A/div (50 mV × 40 dB × 1A/V):

