



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVO-2W-B-N
Type: High Speed Laser Diode Driver
S.N.: 12721
Date: October 28, 2011

Output Amplitude: up to -10A, to 6.2Ω
Pulse Width (FWHM): 4 – 50 ns
Rise Time (20%-80%): ≤ 2.5 ns
Fall Time (80%-20%): ≤ 3.5 ns
PRF: 1 Hz - 20 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

10 kHz, 10 ns, -62V into 6.2 Ohms (-10A),

10 kHz, 50 ns, -62V into 6.2 Ohms (-10A),

10 ns/div. 20 V/div (200 mV × 40 dB):

10 ns/div. 20 V/div (200 mV × 40 dB):

