



info@avtechpulse.com
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
Fax: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AVO-9W-B-P-P2D-AC22
Type: Ultra-High-Speed Laser Diode Driver
S.N.: 13989
Date: June 10, 2020

Output Amplitude: up to +125V to 25Ω
Pulse Width (FWHM): 4 - 50 ns
Rise Time (20%-80%): ≤ 2.5 ns
Fall Time (80%-20%): ≤ 3.5 ns
PRF: 1 Hz – 20 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms


Mainframe output into one of two 50 Ohm loads at 10 kHz, 5 ns, +125V,

Mainframe output into one of two 50 Ohm loads at 10 kHz, 50 ns, +125V,

10 ns/div. 50 V/div (50 mV/div × 60 dB):

10 ns/div. 50 V/div (50 mV/div × 60 dB):





Test method: A very short length of wire is fed through an Integrated Sensor Technologies 711S current probe, and is then inserted between the signal pin socket and a ground pin socket, as shown below. (The specified rise time of the 711S is < 1.3 ns. It will degrade to measured rise time slightly.)



+10A pulse into a 0Ω test load installed on the output module. 10 ns/div, 5 A/div.