



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVOZ-DF5-B-P  
Type: High-Voltage & Current Pulse Generator  
S.N.: 13786  
Date: October 19, 2018

Output Amplitude: up to +250V, to 5Ω  
Pulse Width (FWHM): 50 to 200 ns  
Rise Time (20%-80%): ≤ 15 ns  
Fall Time (80%-20%): ≤ 15 ns  
PRF: 1 Hz - 2 kHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

2 kHz, 200 ns, +250V, into one of ten 50Ω loads,

50 ns/div,  
100 V/div (100 mV/div × 60 dB):

Output of a 711S current probe installed on the  
output module, with the same settings as the  
previous image (2 kHz, 200 ns, +250V),

50 ns/div,  
20 V/div (200 mV/div × 40 dB) = 20 A /div:

