



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVL-2A-W-B-P-M
Type: Ultra-High-Speed Pulse Generator
S.N.: 13070
Date: September 12, 2013

Output Amplitude: up to +160V, to 50Ω
Pulse Width (FWHM): 3 – 400 ns
Rise Time (20%-80%): ≤ 2 ns
Fall Time (80%-20%): ≤ 3 ns
PRF: 1 Hz - 50 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

20 kHz, < 3 ns, > 160V,

50 kHz, 20 ns, > 160V,

2 ns/div. 50 V/div (50 mV/div × 60 dB):

5 ns/div. 50 V/div (50 mV/div × 60 dB):



50 kHz, 400 ns, > 160V,

50 ns/div. 50 V/div (50 mV/div × 60 dB):

