



info@avtechpulse.com  
http://www.avtechpulse.com/


Tel: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
Fax: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AVR-8A-B-P  
Type: High Voltage Pulse Generator  
S.N.: 14099  
Date: January 27, 2021


Rise & Fall Time Test



10 Hz, 2 us, +1 kV into a 50Ω load.  
200 V/div, 400 ns/div.

- a) Output Signal Amplitude: up to +1000V
- b) Pulse Width (FWHM): 200 ns - 200 us, 0.2% duty cycle
- c) Rise Time (20%-80%): < 50 ns
- d) Fall Time (20%-80%): < 50 ns
- e) PRF: 1 Hz - 1 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.

Wide Pulse / Maximum Duty Cycle Test



20 Hz, 100 us, +1 kV into a 50Ω load.  
200 V/div, 20 us/div.

References levels: 20%, 80%.