



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVRK-3-B-P-AC03  
Type: High Voltage Pulse Generator  
S.N.: 13493  
Date: August 31, 2016

Output Amplitude: up to +550V, to 50Ω  
Pulse Width (FWHM): 6 to 35 ns  
Rise Time (20%-80%): ≤ 5 ns  
Fall Time (80%-20%): ≤ 5 or 8 ns  
PRF: 1 Hz - 1 kHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz

Basic specifications: →

Test Waveforms

1 kHz, 8 ns, +550V,

Top (main out): 100 V/div (100 mV/div × 60 dB)  
Bottom (monitor): 20 V/div (200mV/div × 40 dB)  
Both: 5 ns/div.

1 kHz, > 35 ns, > +550V,

Top (main out): 100 V/div (100 mV/div × 60 dB)  
Bottom (monitor): 20 V/div (200mV/div × 40 dB)  
Both: 10 ns/div.

