



info@avtechpulse.com
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada)
or +1-613-686-6675 (Worldwide)

BOX 5120, LCD MERIVALE
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AVRK-4-B-PN-TR-DPF
Type: High Voltage Pulse Generator
S.N.: 14140
Date: June 23, 2021

Output Amplitude: up to $\pm 750V$, to 50Ω
Pulse Width (FWHM): 6 to 20 ns
Rise Time (20%-80%): ≤ 2 ns
Fall Time (80%-20%): varies with PW/amp
PRF: 1 Hz - 1 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz

Basic specifications: →



Test Waveforms

CH1, 1 kHz, > 20 ns, -750V, into 50Ω

CH2, 1 kHz, < 6 ns, +750V, into 50Ω


5 ns/div, 200 V/div (200 mV/div \times 60 dB)

5 ns/div, 200 V/div (200 mV/div \times 60 dB)



Pulse doublet, 1 kHz, both 20 ns, both +750V, into 50Ω

50 ns/div, 200 V/div (200 mV/div × 60 dB)



Pulse doublet, 1 kHz, both 20 ns, both -750V, into 50Ω

50 ns/div, 200 V/div (200 mV/div × 60 dB)

