



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVN-5A-C-P-PN
Type: Ultra-High-Speed Pulse Generator
S.N.: 12871
Date: August 31, 2012

Output Amplitude: up to 20V-30V, to 50Ω
Pulse Width (FWHM): 0.4 - 1 ns, 0.4 – 0.7 ns
Rise Time (20%-80%): ≤ 200 ps
Fall Time (80%-20%): ≤ 300 ps
PRF: 25 - 200 MHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

25 MHz, ~ 400 ps, +25V into 50 Ohms:

25 MHz, ~ 1 ns, > +25V into 50 Ohms:


500 ps/div. 10 V/div (100 mV × 40 dB):

500 ps/div. 10 V/div (100 mV × 40 dB):




100 MHz, ~ 400 ps, +30V into 50 Ohms:

2 ns/div. 10 V/div (100 mV × 40 dB):




100 MHz, ~ 1 ns, > +30V into 50 Ohms:

2 ns/div. 10 V/div (100 mV × 40 dB):




150 MHz, ~ 400 ps, > +30V into 50 Ohms:

1 ns/div. 10 V/div (100 mV × 40 dB):




150 MHz, ~ 1 ns, > +30V into 50 Ohms:

1 ns/div. 10 V/div (100 mV × 40 dB):



200 MHz, < 400 ps, +20V into 50 Ohms:

1 ns/div. 10 V/div (100 mV × 40 dB):



200 MHz, ~ 700 ps, > +20V into 50 Ohms:

1 ns/div. 10 V/div (100 mV × 40 dB):

