



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVP-AV-1-C-2CHPN
Type: Ultra-High-Speed Pulse Generator
S.N.: 12836
Date: June 15, 2012

Output Amplitude: up to 10V, to 50Ω
Pulse Width (FWHM): 0.2 to 4 ns
Rise Time (20%-80%): ≤ 100 ps
Fall Time (80%-20%): ≤ 300 ps
PRF: 1 Hz - 1 MHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

1 MHz, < 200 ps, +10V,

1 MHz, 4 ns, +10V,


500 ps/div. 5 V/div (50 mV × 40 dB):

1 ns/div. 5 V/div (50 mV × 40 dB):




1 MHz, < 200 ps, -10V,

500 ps/div. 5 V/div (50 mV × 40 dB):




1 MHz, 4 ns, -10V,

1 ns/div. 5 V/div (50 mV × 40 dB):



Inter-channel delay at minimum,

20 ns/div. 5 V/div (50 mV × 40 dB):



Inter-channel delay at maximum,

20 ns/div. 5 V/div (50 mV × 40 dB):

