



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVP-AV-2-B-PN-M  
Type: Ultra-High-Speed Pulse Generator  
S.N.: 12254  
Date: June 1, 2009

Output Amplitude: 0 to ±10V, to 50Ω  
Pulse Width (FWHM): 2 to 50 ns  
Rise Time (20%-80%): ≤ 100 ps  
Fall Time (80%-20%): ≤ 200 ps  
PRF: 1 Hz - 50 kHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

10 kHz, 8 ns width, +10V,

10 kHz, 8 ns width, -10V,


2 ns/div. 5 V/div (50 mV × 40 dB):

2 ns/div. 5 V/div (50 mV × 40 dB):



10 kHz, 48 ns width, +10V,

10 ns/div. 5 V/div (50 mV × 40 dB):



10 kHz, 48 ns width, -10V,

10 ns/div. 5 V/div (50 mV × 40 dB):

