



AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
SINCE 1975

□ P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

☒ BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVPP-2-B-P
Type: Ultra-High-Speed Pulse Generator
S.N.: 13134
Date: March 7, 2014



Output Amplitude: up to +20V, to 50Ω
Pulse Width (FWHM): 0.6 – 100 ns
Rise Time (20%-80%): ≤ 200 ps
Fall Time (80%-20%): ≤ 350 ps or 500 ps
PRF: 1 Hz – 100 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →


Test Waveforms

Leading edge at 10 kHz, 100 ns, +20V,
1 ns/div. 10 V/div (100 mV/div × 40 dB):


Trailing edge at 10 kHz, 100 ns, +20V,
1 ns/div. 10 V/div (100 mV/div × 40 dB):



Full pulse at 100 kHz, 0.4 ns, +20V,
 500 ps/div. 10 V/div (100 mV/div × 40 dB):



Full pulse at 100 kHz, 4 ns, +20V,
 1 ns/div. 10 V/div (100 mV/div × 40 dB):



Full pulse at 100 kHz, 10 ns, +20V,

2 ns/div. 10 V/div (100 mV/div × 40 dB):

