



□ P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802


TEL: 1-800-265-6681
FAX: 1-800-561-1970

e-mail: info@avtechpulse.com
http://www.avtechpulse.com/

☒ BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802

PERFORMANCE CHECKSHEET

Model: AV-1020-C-R5-LANB
S.N.: 11023
Date: September 22, 2004




Top: OUT, +10V amplitude, 0V offset, to 50 Ohms
Bottom: TTL-inverted out, to 50 Ohms
Both: Maximum PRF, near minimum PW. 5V/div, 40 ns/div

- a) Output Signal Amplitude: 0 to ±10V
- b) Pulse Width: 50 ns - 500 ms
- c) Rise Time: < 10 ns
- d) Fall Time: < 10 ns
- e) PRF: 1Hz - 10 MHz

f) Jitter, Stability: OK

g) Prime Power: 120/240V AC, 50-60 Hz.



Top: OUT, +10V amplitude, -5V offset, into 50 Ohms. 5 V/div.
Bottom: ECL-inverted out, to 50 Ohms. 0.5 V/div.
Both: 2 ms/div

Reference levels: 10%, 90%