



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265  
TEL: (315) 472-5270  
FAX: (613) 226-2802


TEL: 1-800-265-6681  
FAX: 1-800-561-1970

e-mail: [info@avtechpulse.com](mailto:info@avtechpulse.com)  
<http://www.avtechpulse.com/>

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4  
TEL: (613) 226-5772  
FAX: (613) 226-2802


PERFORMANCE CHECKSHEET

Model: AV-1020-C-R5-LANB  
S.N.: 11024  
Date: September 22, 2004



Top: OUT, +10V amplitude, 0V offset, to 50 Ohms  
Bottom: TTL-inverted out, to 50 Ohms  
Both: Near maximum PRF & minimum PW. 5V/div, 40 ns/div

- a) Output Signal Amplitude: 0 to  $\pm 10V$
- b) Pulse Width: 50 ns - 500 ms
- c) Rise Time: < 10 ns
- d) Fall Time: < 10 ns
- e) PRF: 1Hz - 10 MHz



Top: OUT, +10V amplitude, -5V offset, into 50 Ohms. 5 V/div.  
Bottom: ECL-inverted out, to 50 Ohms. 0.5 V/div.  
Both: 2 ms/div

- f) Jitter, Stability: OK
- g) Prime Power: 120/240V AC, 50-60 Hz.

Reference levels: 10%, 90%