



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802


TEL: 1-800-265-6681
FAX: 1-800-561-1970

e-mail: info@avtechpulse.com
http://www.avtechpulse.com/

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802

PERFORMANCE CHECKSHEET


Model: AVRH-3-B-PN
S.N.: 11090
Date: January 19, 2005



19 Jan 2005
14:16:59

1 kHz, 2.5 us, +3000V into a 10 kΩ load.
1 kV/div, 400 ns/div.

- a) Output Signal Amplitude: 0 to ±3000V, to R ≥ 10 kΩ
- b) Pulse Width (FWHM) : 200 ns – 2.5 us,
- c) Rise Time (20%-80%): < 100 ns
- d) Fall Time (80%-20%): < 100 ns
- e) PRF: 1 Hz - 1 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.



19 Jan 2005
14:18:04

1 kHz, 2.5 us, -3000V into a 10 kΩ load.
1 kV/div, 400 ns/div.

References levels: 20%, 80%.