



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVR-E4-C-P
Type: Ultra-High-Speed Pulse Generator
S.N.: 11601
Date: October 19, 2006

Output Amplitude: 0 to +100V, to 50Ω
Pulse Width (FWHM): 1 – 5 ns
Rise Time (20%-80%): ≤ 400 ps
Fall Time (80%-20%): ≤ 400 ps
PRF: 10 Hz - 100 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

100 kHz, near maximum pulse width and maximum amplitude.

100 kHz, near minimum pulse width and maximum amplitude.

1 ns/div. 50 V/div (50 mV × 60 dB):

1 ns/div. 50 V/div (50 mV × 60 dB):

