



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVO-6A1-B-OS-P-M-S-SCHA  
Type: High-Speed Laser Diode Driver  
S.N.: 11730  
Date: May 16, 2007



Output Amplitude: 0 to +50V, to 50Ω (1A)  
Pulse Width (FWHM): 50 ns – 5 us  
Rise Time (20%-80%): ≤ 1 ns  
Fall Time (80%-20%): ≤ 1 ns  
PRF: 1 Hz – 10 kHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

Leading edge at 10 kHz, 100 ns, +50V,  
2 ns/div. 20 V/div (200 mV × 40 dB):

Trailing edge at 10 kHz, 100 ns, +50V,  
2 ns/div. 20 V/div (200 mV × 40 dB):



Full pulse at 10 kHz, 100 ns, +50V,

20 ns/div. 20 V/div (200 mV × 40 dB):

