



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265


TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-133B
Type: High-Speed Amplifier
S.N.: 11731
Date: April 19, 2007



Fall	Amplitude		Measurements	Main Size
251.57 ps	32.800 mV			2ns/div
				Main Pos
				340.1118ns
			Compare & References	Remove/Clr Pan/Trace 1 Zoom
				Avg (M1) Off
				Main

a) Output Signal Amplitude:
0 to 0.4V, to 50 Ohms

b) Gain: > 30 dB

c) Rise Time (20%-80%): < 0.4 ns

d) Fall Time (20%-80%): < 0.4 ns

e) Bandwidth: 1 - 1000 MHz

f) Jitter, Stability: OK

g) Prime Power: +15V DC

> 0.25V output into 50 Ohms, in response to a ~ 8 mV input pulse.

2 ns/div. 200 mV/div (20 mV × 20 dB).

References levels: 20%, 80%.