



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVP-AV-1-EA-EW-P-NTA-NTB
Type: Ultra-High-Speed Pulse Generator
S.N.: 11898
Date: December 4, 2007

Output Amplitude: 0 to +10V, to 50Ω
Pulse Width (FWHM): 0.2 – 4 ns
Rise Time (20%-80%): ≤ 100 ps
Fall Time (80%-20%): ≤ 200 ps
PRF: 1 Hz - 1 MHz
Jitter, Stability: OK
Prime Power: +15V DC

Basic specifications: →

Test Waveforms

< 0.2 ns pulse width at 100 kHz, > 10V out,

2.5 ns pulse width at 100 kHz, +10V out,

200 ps/div. 5 V/div (50 mV × 40 dB):

500 ps/div. 5 V/div (50 mV × 40 dB):

