



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)


BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-107C-B-PN
Type: Pulsed Constant Current Generator
S.N.: 11996
Date: May 14, 2008

Positive Test



a) Output Signal Amplitude: 0 to ±10A

b) Pulse Width (FWHM): 100 ns to 1 us

c) Rise Time (20%-80%): < 20 ns

d) Fall Time (80%-20%): < 20 ns


e) PRF: 1 Hz – 5 kHz

f) Jitter, Stability: OK

g) Prime Power: 100-240V AC, 50-60 Hz.

100 Hz, 1 us, +1A, +2.5A, +5A and +10A
into a 3.30Ω load installed on the mainframe output.
5 V/div, 200 ns/div.

Negative Test



100 Hz, 1 us, +1A, +2.5A, +5A and +10A
into a 3.30Ω load installed on the mainframe output.
5 V/div, 200 ns/div.

References levels: 20%, 80%.