



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-226-5772 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-226-2802 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVP-AV-HV3-P-UWA-PS15  
Type: Ultra-High-Speed Pulse Generator  
S.N.: 12084  
Date: October 2, 2008

Output Amplitude: 0 to +40V, to 50Ω  
Pulse Width (FWHM): 0.4 – 2 ns  
Rise Time (20%-80%): ≤ 150 ps  
Fall Time (80%-20%): ≤ 300 ps  
PRF: 1 Hz - 1 MHz  
Jitter, Stability: OK  
Prime Power: +15V DC

Basic specifications: →

Test Waveforms

< minimum PW at 10 kHz, +40V.

Maximum PW at 10 kHz, +40V.

500 ps/div. 10 V/div (100 mV × 40 dB):

500 ps/div. 10 V/div (100 mV × 40 dB):

