



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVL-5-B-P
Type: High-Speed High-Voltage Pulse Generator
S.N.: 12173
Date: December 23, 2008


Max. Duty / Amplitude and Rise Time Test



2 kHz, 100 ns, +450V into a 50Ω load.
100 V/div, 20 ns/div.


- a) Output Signal Amplitude: 0 to +450V
- b) Pulse Width (FWHM) : 8 – 100 ns
- c) Rise Time (20%-80%): < 4 ns
- d) Fall Time (80%-20%): < 5 ns
- e) PRF: 1 Hz - 2 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.

Minimum Pulse Width Test



2 kHz, 8 ns, +450V into a 50Ω load.
100 V/div, 20 ns/div.

Short Circuit Test



10 Hz, 100 ns, +450V into a 50Ω load shorted
with a 12" length of patch cord.
200 V/div, 20 ns/div.

Reference levels: 20%, 80%.