



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265


TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-108F-5-B-AC19-AK4-P  
Type: Pulse Constant Current Generator and Laser Diode Driver  
S.N.: 12590  
Date: January 19, 2011



a) Output Signal Amplitude: up to +12.5A

b) Pulse Width (FWHM): 20 us to 1 ms

c) Rise Time (20%-80%): < 5 us


d) Fall Time (20%-80%): < 5 us

e) PRF: 1 Hz - 1 kHz

f) Jitter, Stability: OK

19 Jan 2011 10:30:15  
Top: 1 kHz, 280 us, +12.5A into a 6.54Ω load. 25V/div.  
Bot: Monitor output (1V / 5A). 400 us/div.

g) Prime Power: 100-240V AC, 50-60 Hz.



19 Jan 2011 10:37:11  
Top: 280 Hz, 1 ms, +12.5A into a 6.54Ω load. 25V/div.  
Bot: Monitor output (1V / 5A). 200 us/div.

References levels: 20%, 80%.