



AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
SINCE 1975

P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVMH-3-C-OS-M-P-SCHA
Type: Ultra-High-Speed Pulse Generator
S.N.: 12617
Date: May 25, 2011

Output Amplitude: +15 to +60V, to 50Ω
Pulse Width (FWHM): 450 ps
Rise Time (20%-80%): N/A
Fall Time (80%-20%): N/A
PRF: 3 kHz to 26 MHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms

Top: Main output, 26 MHz, 20 V/div, 5 ns/div.
Bottom: Monitor output, 2 V/div.

Same waveforms, scaled at 1 ns/div:

