



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVO-8C3-B-TRIP-AK3-AK9-TNT-R6-P-TT1
Type: High-Current Pulsed-Voltage Laser Diode Driver
S.N.: 12839
Date: July 12, 2012


Rise & Fall Time Test



Top: 10 Hz, 200 us, 80A into 0.74Ω. 20 V/div, 40 us/div.
Bottom: Monitor output. 2 V/div, 40 us/div.

- a) Output Signal Amplitude: 0 to +60 V, 0 to +80 Amps.
- b) Pulse Width (FWHM) : 2 us - 1 s
- c) Rise Time (20%-80%): < 1.5 us
- d) Fall Time (80%-20%): < 1.5 us
- e) PRF: 1 Hz - 1 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.

Wide Pulse Test



10 Hz, 50 ms, +80A into 0.216Ω with a +10A DC offset.
5 V/div, 40 ms/div.

References levels: 20%, 80%.