



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVOZ-A4-B-P-NOCLZ
Type: High-Speed, High-Current Pulsed-Voltage Laser Diode Driver
S.N.: 12844
Date: July 13, 2012

Wide Pulse Test



100 Hz, 5 us, +100V into a 1.0 Ohm test load.
20 V/div, 1 us/div.

a) Output Signal Amplitude: 0 to +100 V
to ≥ 1.0 Ohms (i.e., 0 to +100 Amps)

b) Pulse Width: 100 ns - 5 us
(maximum duty cycle 0.1%)

c) Rise Time: ≤ 30 ns (20-80%)


d) Fall Time: ≤ 30 ns (80-20%)

e) PRF: 0 - 10 kHz
(maximum duty cycle 0.1%)

f) Jitter, Stability: OK

g) Prime Power: 100-240V AC, 50-60 Hz.

Narrow Pulse Test



100 Hz, 500 ns, +100V into a 1.0 Ohm test load.
20 V/div, 100 ns/div.

References levels: 20%, 80%.