



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVO-9A-B-P1B-T1B-P  
Type: Ultra-High-Speed Laser Diode Driver  
S.N.: 12917  
Date: October 26, 2012



Output Amplitude: up to +13V, to 50Ω  
Pulse Width (FWHM): 0.4 - 4 ns  
Rise Time (20%-80%): ≤ 200 ps  
Fall Time (80%-20%): ≤ 200 ps  
PRF: 1 Hz – 1 MHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →

Test Waveforms


Pulse into 50 Ohm load at 100 kHz, 0.4 ns, +13V,  
1 ns/div. 5 V/div (50 mV × 40 dB):

Pulse into 50 Ohm load at 100 kHz, 4.0 ns, +13V,  
1 ns/div. 5 V/div (50 mV × 40 dB):



“MI” output of AVX-S1-P1B-T1B into 50 Ohms, for +13V, 100 kHz, 4 ns pulse width, with a 1N4148 test diode installed in the output sockets:

1 ns/div. 0.5 V/div (50 mV × 20 dB, ≈ 105 mA/div):



The spike on the leading edge is caused primarily by the short-but-nonzero (~ 1 ns) turn-on time of the 1N4148.