



P.O. BOX 265 OGDENSBURG, NY U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl) FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE OTTAWA, ONTARIO CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-1020-C-R5
Type: General Purpose Pulse Generator
S.N.: 12939
Date: October 1, 2012


Rise & Fall Time Test



Top: Main OUT, +10V, 2 MHz, 200 ns, into 50 Ohms. Bottom: NOT-TTL out. Both: 5 V/div, 100 ns/div.

- a) Output Signal Amplitude: 0 to ±10V
b) Pulse Width (FWHM): 50 ns - 500 ms
c) Rise Time (20%-80%): < 10 ns
d) Fall Time (80%-20%): < 10 ns
e) PRF: 1Hz - 10 MHz
f) Jitter, Stability: OK
g) Prime Power: 100-240V AC, 50-60 Hz.

Wide Pulse Test



Top: Main OUT, +10V with -5V offset, into 50Ω. 5V/div. Bottom: NOT-ECL out. 500 mV/div. Both: 2 ms/div.

References levels: 20%, 80%.