



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVM-1-C-P
Type: Ultra-High-Speed Pulse Generator
S.N.: 12944
Date: November 27, 2012

Output Amplitude: up to +5V, to 50Ω
Pulse Width (FWHM): 0.25 – 6 ns
Rise Time (20%-80%): ≤ 100 ps
Fall Time (80%-20%): ≤ 250 ps
PRF: to 25 MHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

Medium pulse width test:

12 MHz, > +5V, 1.5 ns PW.
500 ps/div. 2 V/div (20 mV/div × 40 dB).


Wide pulse width test:

12 MHz, > +5V, 6 ns PW.
1 ns/div. 2 V/div (20 mV/div × 40 dB).



Rise time test:

12 MHz, > +5V, 1.5 ns PW.
 100 ps/div. 2 V/div (20 mV/div × 40 dB).



Narrow pulse test:

12 MHz, > +5V, < minimum PW.
 200 ps/div. 2 V/div (20 mV/div × 40 dB).

