



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265


TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-106A-B-M-P-FPA  
Type: Pulsed Laser Diode Driver  
S.N.: 12996  
Date: March 13, 2013



+3A, +10A, +30A into a 0.956 Ohm load installed on the rear panel. 50 us pulse width. 10 V/div, 10 us/div.

a) Output Signal Amplitude: up to +30A

b) Pulse Width (FWHM): 0.5 to 50 us


c) Rise Time (20%-80%): < 50 ns

d) Fall Time (80%-20%): < 50 ns

e) PRF: 1 Hz – 1 kHz

f) Jitter, Stability: OK

g) Prime Power: 100-240V AC, 50-60 Hz.



+3A into the supplied AV-CTL2-ENC test load (~1.8Ω).  
5 us pulse width. 2 V/div, 1 us/div.

References levels: 20%, 80%.