



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265


TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET


Model: AV-107D-B-P
Type: High-Speed, High-Current Laser Diode Driver
S.N.: 13145
Date: April 16, 2014



- a) Output Signal Amplitude: up to +20A
- b) Pulse Width (FWHM): 50 ns – 5 us
- c) Rise Time (20%-80%): < 30 ns
- d) Fall Time (80%-20%): < 30 ns
- e) PRF: 1 Hz - 500 Hz

+2A, +5A, +10A and +20A into a 0.965Ω load installed on the end of the AV-CLZ1-100 transmission line cable assembly. 5 V/div, 1 us/div.

- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.



Top: +20A into a 0.965Ω load installed on the end of the AV-CLZ1-100 transmission line. 10V/div.
Bottom: Monitor output into 50Ω. 1 V/div.
Both: 200 ns/div.

References levels: 20%, 80%.