



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-144B1-HUC
Type: High-Speed Pulse Generator Module
S.N.: 13277
Date: April 21, 2015



Output Amplitude: +100V, to 50Ω
Pulse Width (FWHM): 30 ns – 1 ms
Rise Time (20%-80%): ≤ 2 ns
Fall Time (80%-20%): ≤ 2 ns
Duty cycle: 5% maximum
Jitter, Stability: OK
Prime Power: +24V, -24V, +115V DC

Basic specifications: →

Test Waveforms

Leading edge at 1 kHz, > 10 us PW, +100V,
10 ns/div. 50 V/div (50 mV/div × 60 dB):

Trailing edge at 1 kHz, > 10 us PW, +100V,
10 ns/div. 50 V/div (50 mV/div × 60 dB):



Full pulse at 100 kHz, 30 ns PW, +100V,

5 ns/div. 50 V/div (50 mV/div × 60 dB):

