



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-107C-B-P-AC03-R5-VXI  
Type: Pulsed Laser Diode Driver  
S.N.: 13313  
Date: August 10, 2015

Rise & Fall Time Test



+0.3 / +1 / +2 / +5 / +10A into a 3.3 Ohm load installed on the rear panel. 5 V/div, 200 ns/div.

a) Output Signal Amplitude: up to +10A

b) Pulse Width (FWHM): 100 ns to 1 us

c) Rise Time (20%-80%): < 20 ns


d) Fall Time (80%-20%): < 20 ns

e) PRF: 1 Hz – 5 kHz

f) Jitter, Stability: OK

g) Prime Power: 100-240V AC, 50-60 Hz.

Wide Pulse Test



Top: +10A into the supplied AV-CTL1-ENC test load (1.0 Ohms). 1 us pulse width. 5 V/div, 200 ns/div.  
Bottom: Monitor output into 50Ω.

References levels: 20%, 80%.