



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265


TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/


PERFORMANCE CHECKSHEET

Model: AV-156E-B  
Type: Dual-Channel Pulsed-Constant-Current Generator  
S.N.: 13402  
Date: February 19, 2016



Top: OUT1, 5A into 5Ω load, 10 ms PW, 70 ms delay  
Bottom: OUT2, 5A into 5Ω load, 10 ms PW  
Both: 10 V/div, 10 ms/div, PRF = 1 Hz.

- a) Output Signal Amplitude: 0 - 5A
- b) Pulse Width (FWHM): 1 - 100 ms
- c) Rise Time (20%-80%): < 10 us
- d) Fall Time (80%-20%): < 10 us
- e) PRF: 1 - 100 Hz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V, 50-60 Hz
- h) Inter-channel delay: 0 - 1000 ms



Top: OUT2, 5A into 5.02Ω load, 10 ms PW, 10 V/div.  
Bottom: MON2 into open circuit, 2V/div.  
Both: PRF = 1 Hz, 10 us/div.

Waveform references levels: 20%, 80%.