



P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AV-109F-3-B-P-AK3-AK9
Type: Pulse Constant Current Generator and Laser Diode Driver
S.N.: 13522
Date: December 5, 2016


Rise Time Test



Top: 1 kHz, 75% duty, +50A into 0.0988Ω (AV-HTL-0R1-HLZ). 2V/div (20 A/div), 200 us/div.
Bot: Monitor output (2.5V / 50A).

- a) Output Signal Amplitude: up to +50A
- b) Pulse Width (FWHM): 10 us to 1 sec
- c) Rise Time (20%-80%): < 10 us
- d) Fall Time (20%-80%): < 10 us
- e) PRF: 1 Hz - 1 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.

Wide Pulse Test



Top: 10 Hz, 75% duty, +50A into 0.0988Ω (AV-HTL-0R1-HLZ). 2V/div (20 A/div), 20 ms/div.
Bot: Monitor output (2.5V / 50A).

References levels: 20%, 80%.