



P.O. BOX 265 OGDENSBURG, NY U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl) FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)


BOX 5120, LCD MERIVALE OTTAWA, ONTARIO CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET

Model: AVO-6HZ-B-PN-M-LEHB
Type: High-Speed High-Power Laser Diode Driver
S.N.: 13571
Date: July 11, 2017


Rise & Fall Time Test (with Output Module)



+10A, 1 us, 100 Hz. Attached single load on output module = 4.99Ω. Current measured with a Tektronix CT2 probe. 5 A/div, 200 ns/div.

- a) Output Signal Amplitude: up to ±105V
b) Pulse Width (FWHM): 50 ns - 50 us, 1% duty cycle
c) Rise Time (20%-80%): < 15 ns
d) Fall Time (20%-80%): < 15 ns
e) PRF: 1 Hz - 100 kHz
f) Jitter, Stability: OK
g) Prime Power: 100-240V AC, 50-60 Hz.


Rise & Fall Time Test (without Output Module)




100 Hz, 500 ns, +100V into one of ten 50Ω loads attached to the rear-panel outputs. 20 V/div, 100 ns/div.

References levels: 20%, 80%.

Wide Pulse Tests



100 Hz, 5 us, -100V into one of ten 50Ω loads attached to the rear-panel outputs.
20 V/div, 1 us/div.



1000 Hz, 50 us, +100V into one of ten 50Ω loads attached to the rear-panel outputs.
20 V/div, 200 us/div.