



P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265


TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)  
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE  
OTTAWA, ONTARIO  
CANADA K2C 3H5

info@avtechpulse.com - http://www.avtechpulse.com/

PERFORMANCE CHECKSHEET


Model: AV-108F-5-B-AC19-AK4-P  
Type: Pulse Constant Current Generator and Laser Diode Driver  
S.N.: 13789  
Date: October 23, 2018



23 Oct 2018  
11:09:33

Top: 1 kHz, 280 us, +12.5A into a 6.51Ω load. 25V/div.  
Bot: Monitor output (1V / 5A). 400 us/div.

- a) Output Signal Amplitude: up to +12.5A
- b) Pulse Width (FWHM): 20 us to 1 ms
- c) Rise Time (20%-80%): < 5 us
- d) Fall Time (20%-80%): < 5 us
- e) PRF: 1 Hz - 1 kHz
- f) Jitter, Stability: OK
- g) Prime Power: 100-240V AC, 50-60 Hz.



23 Oct 2018  
11:10:36

Top: 280 Hz, 1 ms, +12.5A into a 6.51Ω load. 25V/div.  
Bot: Monitor output (1V / 5A). 200 us/div.

References levels: 20%, 80%.