



info@avtechpulse.com
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
Fax: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AVR-E3-B-PN-W2
Type: Ultra-High-Speed Pulse Generator
S.N.: 13897
Date: June 20, 2019

Output Amplitude: up to $\pm 100V$, to 50 Ω
Pulse Width (FWHM): 50 ns to 5 μs
Rise Time (20%-80%): ≤ 500 ps
Fall Time (80%-20%): ≤ 1 ns
PRF: 1 Hz - 20 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz

Basic specifications: →



Test Waveforms

20 kHz, 50 ns, +100V, full pulse,

10 ns/div. 50 V/div (50 mV/div \times 60 dB):


20 kHz, 500 ns, +100V, rising edge,

1 ns/div. 50 V/div (50 mV/div \times 60 dB):




10 kHz, 5 us, +100V, full pulse,

1 us/div. 50 V/div (50 mV/div × 60 dB):




20 kHz, 50 ns, -100V, full pulse,

10 ns/div. 50 V/div (50 mV/div × 60 dB):



20 kHz, 500 ns, -100V, rising edge,
 1 ns/div. 50 V/div (50 mV/div × 60 dB):



10 kHz, 5 us, -100V, full pulse,
 1 us/div. 50 V/div (50 mV/div × 60 dB):

