



info@avtechpulse.com
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
Fax: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

BOX 5120, LCD MERIVALE
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET


Model: AVX-T
Type: Ultra-High-Speed Bias Tee
S.N.: 14060
Date: September 23, 2020

Basic specifications -


Pulse/DC voltage limit: 200V
DC current limit: 0.5A
Pulse width range: 0.2 – 50 ns
Rise time (20%-80%): < 60 ps

Rise Time Test

98.41 ps rise time, -7V input to AVX-T,
1 ns/div. 2 V/div (200 mV/div × 20 dB):



Corresponding output of AVX-T with +7V DC bias added,
1 ns/div. 2 V/div (200 mV/div × 20 dB):




The output rise time should be less than $\sqrt{(98.41\text{ps}^2 + 60\text{ps}^2)} = 115.3 \text{ ps}$. The measured rise time does satisfy this limit.

Maximum Amplitude / PW / Offset Test

200V. 50 ns input to AVX-T,

10 ns/div. 50 V/div (50 mV/div × 60 dB):



Corresponding output of AVX-T with +25V DC bias added,

10 ns/div. 50 V/div (50 mV/div × 60 dB):

