



info@avtechpulse.com
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada)
or +1-613-686-6675 (Worldwide)

BOX 5120, LCD MERIVALE
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AVR-E3-B-P-W1-OT
Type: Ultra-High-Speed Pulse Generator
S.N.: 14187
Date: December 10, 2021

Output Amplitude: up to +100V, to 50Ω
Pulse Width (FWHM): 1 – 200 ns
Rise Time (20%-80%): ≤ 500 ps
Fall Time (80%-20%): ≤ 1 ns
PRF: 1 Hz - 100 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

100 kHz, < 1 ns, > +100V,

100 kHz, 10 ns, > +100V.


2 ns/div. 50 V/div (50 mV/div × 60 dB):

2 ns/div. 50 V/div 50 mV/div × 60 dB):




100 kHz, 200 ns, +100V, leading edge,

5 ns/div. 50 V/div (50 mV/div × 60 dB):



10 kHz, 200 ns, +100V, trailing edge,

5 ns/div. 50 V/div (50 mV/div × 60 dB):



10 kHz, 200 ns, > +100V, full pulse,

50 ns/div. 50 V/div (50 mV/div × 60 dB):

