



info@avtechpulse.com
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada)
or +1-613-686-6675 (Worldwide)

BOX 5120, LCD MERIVALE
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AVR-E3A-B-PN-W1-CC1-AC03
Type: Ultra-High-Speed Pulse Generator
S.N.: 14391
Date: November 16, 2023

Output Amplitude: up to $\pm 100V$, to 50 Ω
Pulse Width (FWHM): 3 – 500 ns
Rise Time (20%-80%): ≤ 1.5 ns
Fall Time (80%-20%): ≤ 2.5 ns
PRF: 1 Hz - 200 kHz
Jitter, Stability: OK
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

10 kHz, < 3 ns, -100V,


10 kHz, 8 ns, +100V.

2 ns/div. 50 V/div (50 mV/div \times 60 dB):


2 ns/div. 50 V/div 50 mV/div \times 60 dB):




10 kHz, 50 ns, +100V, full pulse,
 10 ns/div. 50 V/div (50 mV/div × 60 dB):



10 kHz, 500 ns, -100V, full pulse,
 50 ns/div. 50 V/div (50 mV/div × 60 dB):



20 kHz, 200 ns, +100V, leading edge,
 10 ns/div. 50 V/div (50 mV/div × 60 dB):



20 kHz, 200 ns, +100V, trailing edge,
 10 ns/div. 50 V/div (50 mV/div × 60 dB):

