



info@avtechpulse.com  
http://www.avtechpulse.com/

Tel: 888-670-8729 (USA & Canada)  
or +1-613-686-6675 (Worldwide)

BOX 5120, LCD MERIVALE  
OTTAWA, CANADA K2C3H5

PERFORMANCE CHECKSHEET

Model: AVI-V-HV2B-B-P  
Type: Ultra-High-Speed Pulse Generator  
S.N.: 14434  
Date: June 11, 2024

Output Amplitude: up to +100V, to 50Ω  
Pulse Width (FWHM): 4 – 100 ns  
Rise Time (20%-80%): ≤ 600 ps  
Fall Time (80%-20%): ≤ 4 ns  
PRF: 1 Hz - 20 kHz  
Jitter, Stability: OK  
Prime Power: 100-240V AC, 50-60 Hz.

Basic specifications: →



Test Waveforms

10 kHz, < 4 ns, > +100V,

10 kHz, 10 ns, > +100V,


2 ns/div. 50 V/div (50 mV/div × 60 dB):

2 ns/div. 50 V/div (50 mV/div × 60 dB):



10 kHz, 25 ns, > +100V,

5 ns/div. 50 V/div (50 mV/div × 60 dB):



10 kHz, > 100 ns, > +100V,

20 ns/div. 50 V/div (50 mV/div × 60 dB):

