



AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
SINCE 1975

□ P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802

TEL: 1-800-265-6681
FAX: 1-800-561-1970
U.S.A. & CANADA

e-mail: info@avtechpulse.com

✕ BOX 5120 STN. F
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802

Model AV-133B

The Model AV-133B amplifier is designed to amplify nanosecond rise time baseband pulses in the pulse width range of about 500 ps to 500 ns and CW signals in the frequency range of 1.0 MHz to 1.0 GHz. The basic specifications for the unit are as follows:

Gain:	» 30 dB
Peak output voltage:	± 0.4 Volt
Impedance level:	50 Ohms nominal
Input VSWR:	≤ 2.5:1
Output VSWR:	≤ 2.5:1
Max. noise figure:	2.0 dB
Rise time:	≤ 400 ps
Prime power:	+15 VDC 40 mA max
Connectors:	SMA
Size:	1.4 x 1.1 x 2.3 inches

Dec 14/95

Disc - AV -

Name - 133B .INS

File saved in Word as of Oct 16/97

File: C:\INSTRUCT\AV-1\133B.DOC

Note: File is adjusted in Word.