



AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
SINCE 1975

☐ P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802

TEL: 1-800-265-6681
FAX: 1-800-561-1970
U.S.A. & CANADA

e-mail: info@avtechpulse.com

☒ BOX 5120 STN. F
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802

Model AV-131B

The Model AV-131B amplifier is designed to amplify nanosecond rise time baseband pulses in the pulse width range of about 1 ns to 500 ns and CW signals in the frequency range of 1.0 MHz to 500 MHz. The basic specifications for the unit are as follows:

Gain:	≥ 40 dB
Peak output voltage:	± 1.0 Volt
Impedance level:	50 Ohms nominal
Input VSWR:	≤ 2.5:1
Output VSWR:	≤ 2.5:1
Max. noise figure:	3.0 dB
Rise time:	≤ 1 ns
Prime power:	+15 VDC 100 mA max
Connectors:	SMA
Size:	1.4 x 1.1 x 2.3 inches

CAUTION: The input to this amplifier does not include any overload protection and so it may be damaged if subjected to high amplitude spurious outputs such as those provided by some PMT. The warranty does not apply to such failures.

March 99