

AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS SINCE 1975

P.O. BOX 265 OGDENSBURG, NY U.S.A. 13669-0265 TEL: (315) 472-5270 FAX: (613) 226-2802 TEL: 1-800-265-6681 FAX: 1-800-561-1970

e-mail: info@avtechpulse.com http://www.avtechpulse.com P.O. BOX 5120 STN. F OTTAWA, ONTARIO CANADA K2C 3H4 TEL: (613) 226-5772 FAX: (613) 226-2802

Model AV-135B

The Model AV-135B amplifier is designed to amplify nanosecond rise time baseband pulses in the pulse width range of about 500 ps to 500 ns and CW signals in the frequency range of 1.0 MHz to 2.5 GHz. The basic specifications for the unit are as follows:

Gain: \geq 34 dB

Peak output voltage: ±1.0 Volt

Impedance level: 50 Ohms nominal

Input VSWR: $\leq 2.5:1$

Output VSWR: $\leq 2.5:1$

Max. noise figure: 2.8 dB

Rise time: $\leq 300 \text{ ps}$

Prime power: +15 VDC 130 mA max

Connectors: SMA

Size: 1.4 x 1.1 x 2.3 inches

<u>CAUTION</u>: The input to this amplifier does not include any overload protection and so it may be damaged if subjected to high amplitude spurious outputs such as those provided by some PMT. The warranty does not apply to such failures.