



AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
SINCE 1975

□ P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802

TEL: 1-800-265-6681
FAX: 1-800-561-1970

e-mail: info@avtechpulse.com
http://www.avtechpulse.com

□ P.O. BOX 5120 STN. F
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802

Model AV-135A

The Model AV-135A amplifier is designed to amplify nanosecond rise time baseband pulses in the pulse width range of about 500 ps to 500 ns and CW signals in the frequency range of 1.0 MHz to 2.8 GHz. The basic specifications for the unit are as follows:

Gain:	≥ 26 dB
Peak output voltage:	±0.2 Volt
Impedance level:	50 Ohms nominal
Input VSWR:	≤ 2.5:1
Output VSWR:	≤ 2.5:1
Maximum noise figure:	2.8 dB
Dynamic range:	≥ 60 dB
Rise time:	≤ 250 ps
Prime power:	+15 VDC 20 mA max
Connectors:	SMA
Size:	1.4" x 1.1" x 2.3"

CAUTION: The input to this amplifier does not include any overload protection and so it may be damaged if subjected to high amplitude spurious outputs such as those provided by some PMT. The warranty does not apply to such failures.