



# AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS  
SINCE 1975

□ P.O. BOX 265  
OGDENSBURG, NY  
U.S.A. 13669-0265  
TEL: (315) 472-5270  
FAX: (613) 226-2802

TEL: 1-800-265-6681  
FAX: 1-800-561-1970

e-mail: [info@avtechpulse.com](mailto:info@avtechpulse.com)  
<http://www.avtechpulse.com>

□ P.O. BOX 5120 STN. F  
OTTAWA, ONTARIO  
CANADA K2C 3H4  
TEL: (613) 226-5772  
FAX: (613) 226-2802

## Model AV-143B

### Specifications

The Model AV-143B amplifier is designed to amplify bipolar baseband pulses in the pulse width range of about 100 ns and higher and CW signals in the frequency range of DC to 10 MHz. The basic specifications for the unit are as follows:

Gain:	x 5 (voltage)
Bandwidth:	DC to 10 MHz
Peak output voltage (to 50 Ohms or higher):	± 20 Volts
Rise time:	≤ 50 ns
Input impedance:	1 K
Prime power:	±24V, 600 mA (max)
Connectors:	BNC
Size:	1.7 x 2.6 x 4.3 inches

- CAUTION:**
- 1) The module should be attached to a heat sink capable of dissipating at least 15 Watts.
  - 2) The unit may be damaged if operated into a short circuit. Such failures are not covered by the warranty.
  - 3) DC Offset on the output may be set to zero using the ten-turn OS trim pot. The Offset was set to zero at the time of shipping.

Jan. 15/2001  
(ed. A)