



AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
SINCE 1975

P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265

TEL: 888-670-8729 (USA & Canada) or +1-613-686-6675 (Intl)
FAX: 800-561-1970 (USA & Canada) or +1-613-686-6679 (Intl)

info@avtechpulse.com - <http://www.avtechpulse.com/>

BOX 5120, LCD MERIVALE
OTTAWA, ONTARIO
CANADA K2C 3H4

AVX-SP-2 Power Splitter

INSTRUCTIONS

The AVX-SP-2 power splitter is designed to be used with the AVI, AVMR, AVR-E, AV-1000 and AVL series of pulse generators. The output at the + terminal is of the same polarity as the input applied at the IN terminal while the output at the – terminal is inverted with respect to the IN terminal. The magnitudes of the outputs at the + and – terminals are both equal to one half the magnitude at the IN terminal. Note that the two outputs require 50 Ohm loads.

Rise Time:	≤ 300 ps
Load Impedance:	50 Ohm
Input Impedance:	50 Ohm
Connectors:	SMA
Max. Input Voltage:	350 Volts
Max Average Power:	1/2 Watt
Max. Pulse Width:	100 ns
Size (in):	1.5 x 1.1 x 0.9
Chassis Material:	Cast aluminum, blue enamel