



AVTECH ELECTROSYSTEMS LTD.

NANOSECOND WAVEFORM ELECTRONICS
SINCE 1975

□ P.O. BOX 265
OGDENSBURG, NY
U.S.A. 13669-0265
TEL: (315) 472-5270
FAX: (613) 226-2802

TEL: 1-800-265-6681
FAX: 1-800-561-1970

e-mail: info@avtechpulse.com
<http://www.avtechpulse.com>

□ P.O. BOX 5120 STN. F
OTTAWA, ONTARIO
CANADA K2C 3H4
TEL: (613) 226-5772
FAX: (613) 226-2802

AVX-SP-4-T Power Splitter

INSTRUCTIONS

The AVX-SP-4 power splitter is designed to be used with the AVI, AVK, AVN, AVM and AVP series of pulse generators and AVH series of impulse generators. The output at the + terminal is of the same polarity as the input applied at the IN terminal while the output at the – terminal is inverted with respect to the IN terminal. The magnitudes of the outputs at the + and – terminals are both equal to one half the magnitude at the IN terminal.

A DC offset may be applied to the + output by connecting the desired DC potential to the DC+ solder terminal. Likewise, a DC offset may also be applied to the – output by connecting the desired DC potential to the DC – solder terminal.

Rise Time:	≤ 100 psec
Impedance:	50 Ohm
Connectors:	SMA
Max. Input Voltage:	50 Volts
Max. Pulse Width:	10 nsec
Size (in):	1.5 x 1.1 x 0.9
Chassis Material:	Cast aluminum, blue enamel
DC Offset:	± 50 Volts, 200 mA max.